WINCOR NIXDORF

ProCash 2350xe

Multifunction ATM

Freestanding island drive-up system

- Extremely robust system design
- Bundle output up to 60 notes
- Optimized cash management
- Designed for use by people with disabilities
- Intelligent cash and check deposits
- Comprehensive security solutions
- Open hardware and software architectures
- Project-specific solutions

WINCOR NIXDORF

Technical Data

ProCash 2350xe

Multifunction ATM

The ProCash 2350xe island drive-up system guarantees around-the-clock service under difficult conditions, too.

A sunlight display, resistant materials and a variety of security options meet the increased demands placed on an automated teller machine that is completely free-standing.

This island drive-up system also supports automated deposits of bundles of banknotes and checks.

DISPLAY

Various VGA, SVGA and XGA resolutions implemented on one display via autoscaling

- 8 stainless steel softkeys
- Touchscreen
- 12.1" sunlight TFT LCD
- Privacy display filter

KEYBOARD

- Encrypting PIN pad (EPP V5 PCI)
- PIN shield (VISA-compliant)

CARD HANDLING

- Motorized hybrid card reader
- EMV 2000-certified
- Card retracted if not removed
- Card returned if power fails
- Various card retract compartments

CASH DISPENSING

- Up to 4 cassettes (sealable)
- Max. filling height per cassette: 310 mm
- Note reject/bundle retract, storage in separate compartments
- Cassettes with lock
- Cassettes with filling level recognition
- Cassette presetting

SECURITY

- Intruder alarm
- Portrait camera
- Uninterruptible power supply
- Tamperproof card slot
- Antiskimming device
- Anti-Lebanese loop card reader
- Banknote staining technology

SAFES

- UL 291 Level 1

PRINTERS

- Receipt and journal printer
- Statement/information printer

(Dot matrix or thermal technology both)

ENVELOPE DEPOSITS

- Integrated envelope dispensing
- Transaction data printed in one line
- Capacity: Up to 200 or 300 envelopes depending on the deposit compartment, optional security compartment

CASH/CHECK DEPOSIT MODULE

Banknote processing

- Input of bundles of up to 50 notes (unsorted)
- Up to 2 cassettes (sealable)
- Max. filling height per cassette: 215 mm
- Cassettes with lock
- Separate compartment for counterfeits
- Separate compartment for retracts
- Banknote validation in compliance with ECB article 6
- Metal detection

Check deposits

- Input of bundles of up to 50 checks (unsorted)
- Up to 2 cassettes (sealable)
- Max. filling height per cassette: 215 mm
- Cassettes with lock
- Scanner module for single or bundled checks
  - MICR (E13B or CMC7)
  - OCR image processing

MARKETING FEATURES

- Illuminated logo panel
- Optical indicators (MEIs) at all input/output modules
- Info panel for card symbols

AUDIO

- Loudspeakers
- Headset jack

OPERATING SYSTEM

- Windows XP

POWER SUPPLY

- 110 – 120 V~/220 – 240 V~, 50 – 60 Hz

TEMPERATURE RANGE

- + 5°C to + 40°C
- - 40°C to + 50°C (with climate control unit)

RELATIVE HUMIDITY

- 5 % to 85 %

INSTALLATION

- Frontload
- Outdoors

APPROVALS

Published by
Wincor Nixdorf International GmbH • Banking Division

Order No. R10141-J-Z744-2-7600
Printed in Germany, June 2007 , s

Heinz-Nixdorf-Ring 1 • D-33106 Paderborn • Germany
Phone: +49 (0) 52 51 / 6 93-33 01
Fax: +49 (0) 52 51 / 6 93-59 18
Info.Banking@wincor-nixdorf.com
www.wincor-nixdorf.com

© Wincor Nixdorf International GmbH
ProCash® is a registered trademark of Wincor Nixdorf International GmbH

All rights, including rights created by patent grant or registration of a utility model or design, are reserved.Delivery subject to availability, subject to change for technical reasons.